



Identification	(CE) 1272/2008	Nota	%
CAS: 67-64-1 EC: 200-662-2 REACH: 01-2119471330-49-xxxx  ACETON	GHS02, GHS07 Dgr Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH:066		30 <= x % < 50
CAS: 67-63-0 EC: 200-661-7 REACH: 01-2119457558-25-xxxx  PROPAN-2-OL	GHS02, GHS07 Dgr Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336		10 <= x % < 20
CAS: 106-97-8 EC: 203-448-7 REACH: 01-2119474691-32-XXXX  CAS: 74-98-6 EC: 200-827-9 REACH: 01-2119486944-21-XXX  PROPELLANT : PROPANE BUTANE	GHS02 Dgr Flam. Gas 1, H220 Press. Gas, H280		30 <= x % < 50

## SECTION 4: FIRST AID MEASURES

### 4.1. Description of first aid measures

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

#### In the event of exposure by inhalation :

In the event of massive inhalation of dust, remove the person exposed to fresh air. Keep warm and at rest.

If the person is unconscious, place in recovery position. Notify a doctor in all events, to ascertain whether observation and supportive hospital care will be necessary.

If breathing is irregular or has stopped, effect mouth-to-mouth resuscitation and call a doctor.

#### In the event of splashes or contact with eyes :

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.

If there is any redness, pain or visual impairment, consult an ophthalmologist.

#### In the event of splashes or contact with skin :

Remove contaminated clothing and wash the skin thoroughly with soap and water or a recognised cleaner.

Watch out for any remaining product between skin and clothing, watches, shoes, etc.

In the event of an allergic reaction, seek medical attention.

#### In the event of swallowing :

Seek medical attention, showing the label.

### 4.2. Most important symptoms and effects, both acute and delayed

No data available.

### 4.3. Indication of any immediate medical attention and special treatment needed

No data available.

## SECTION 5: FIREFIGHTING MEASURES

### 5.1. Extinguishing media

Flammable.

Chemical powders, carbon dioxide and other extinguishing gas are suitable for small fires.

Keep packages cool when in the vicinity of flames.

Suitable methods of extinction

Prevent the effluent of fire-fighting measures from entering drains or waterways.

### 5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)
- carbon dioxide (CO2)

### **5.3. Advice for firefighters**

Fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.

## **SECTION 6: ACCIDENTAL RELEASE MEASURES**

### **6.1. Personal precautions, protective equipment and emergency procedures**

Consult the safety measures listed under headings 7 and 8.

#### **For non first aid worker**

Avoid inhaling the vapors.

Avoid any contact with the skin and eyes.

Avoid inhaling dust.

If a large quantity has been spilt, evacuate all personnel and only allow intervention by trained operators equipped with safety apparatus.

#### **For first aid worker**

First aid workers will be equipped with suitable personal protective equipment (See section 8).

### **6.2. Environmental precautions**

Prevent any material from entering drains or waterways.

### **6.3. Methods and material for containment and cleaning up**

Retrieve the product by mechanical means (sweeping/vacuuming).

### **6.4. Reference to other sections**

No data available.

## **SECTION 7: HANDLING AND STORAGE**

### **7.1. Precautions for safe handling**

Requirements relating to storage premises apply to all facilities where the mixture is handled.

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

#### **Fire prevention :**

Handle in well-ventilated areas.

Prevent the formation of flammable or explosive concentrations in air and avoid vapor concentrations higher than the occupational exposure limits.

Do not spray on a naked flame or any incandescent material.

Do not pierce or burn, even after use.

Use the mixture in premises free of naked flames or other sources of ignition and ensure that electrical equipment is suitably protected.

Keep packages tightly closed and away from sources of heat, sparks and naked flames.

Do not use tools which may produce sparks. Do not smoke.

Prevent access by unauthorised personnel.

#### **Recommended equipment and procedures :**

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Do not breathe in aerosols.

Avoid inhaling vapors.

Avoid inhaling vapors. Carry out any industrial operation which may give rise to this in a sealed apparatus.

Provide vapor extraction at the emission source and also general ventilation of the premises.

Also provide breathing apparatus for certain short tasks of an exceptional nature and for emergency interventions.

In all cases, recover emissions at source.

Avoid skin and eye contact with this mixture.

#### **Prohibited equipment and procedures :**

No smoking, eating or drinking in areas where the mixture is used.

### **7.2. Conditions for safe storage, including any incompatibilities**

#### **Storage**

Keep the container tightly closed in a dry, well-ventilated place.

Keep away from food and drink, including those for animals.

Keep away from all sources of ignition - do not smoke.

Keep well away from all sources of ignition, heat and direct sunlight.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C.

**Packaging**

Always keep in packaging made of an identical material to the original.

**7.3. Specific end use(s)**

Product for NON DESTRUCTIVE TESTING

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION****8.1. Control parameters**

ACETON

VME = 1210mg/m<sup>3</sup>

PROPAN-2-OL

VME = 980mg/m<sup>3</sup>

**8.2. Exposure controls**

Personal protection measures, such as personal protective equipment

Pictogram(s) indicating the obligation of wearing personal protective equipment (PPE) :



Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

**Eye / face protection**

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles with protective sides accordance with standard EN166.

In the event of high danger, protect the face with a face shield.

Before handling powders or dust emission, wear mask goggles in accordance with standard EN166.

Prescription glasses are not considered as protection.

Individuals wearing contact lenses should wear prescription glasses during work where they may be exposed to irritant vapours.

Provide eyewash stations in facilities where the product is handled constantly.

**Hand protection**

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN ISO 374-1.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

**Body protection**

Avoid skin contact.

Wear suitable protective clothing.

Suitable type of protective clothing :

In the event of substantial spatter, wear liquid-tight protective clothing against chemical risks (type 3) in accordance with EN14605/A1 to prevent skin contact.

Wear protective clothing against solid chemicals and particles suspended in the air (type 5) in accordance with standard EN13982-1/A1 to prevent skin contact.

In the event of a risk of splashing, wear protective clothing against chemical risks (type 6) in accordance with EN13034/A1 to prevent skin contact.

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

**Respiratory protection**

Avoid inhaling vapors.

Avoid inhaling dust.

If the ventilation is insufficient, wear appropriate breathing apparatus.

When workers are confronted with concentrations that are above occupational exposure limits, they must wear a suitable, approved, respiratory protection device.

Type of FFP mask :

Wear a disposable half-mask dust filter in accordance with standard EN149/A1.

Wear a disposable half-mask aerosol filter in accordance with standard EN149/A1.

Category : - FFP1

Anti-gas and vapour filter(s) (Combined filters) in accordance with standard EN14387 :

- AX

Particle filter according to standard EN143 :

- P1 (White)

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

Physical state	Liquid
Colour	Colorless liquid
Density	0.79
Boiling point / boiling range	56°C
Autoignition Temperature	> 230°C
Flash point	< 0°C
Explosion hazards, lower explosion limit (%):	2.5%
Explosion hazards, upper explosion limit (%):	14.3%

### 9.2. Other information

**9.2.1. Information with regard to physical hazard classes** No data available.

**9.2.2. Other safety characteristics** No data available.

## SECTION 10: STABILITY AND REACTIVITY

### 10.1. Reactivity

No data available.

### 10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

### 10.3. Possibility of hazardous reactions

No data available.

### 10.4. Conditions to avoid

Any apparatus likely to produce a flame or to have a metallic surface at high temperature (burners, electric arcs, furnaces etc.) must not be allowed on the premises.

Avoid :

- heating
- heat
- formation of dusts

Dusts can form an explosive mixture with air.

### 10.5. Incompatible materials

No data available.

### 10.6. Hazardous decomposition products

The thermal decomposition may release/form :

carbon monoxide (CO)

carbon dioxide (CO2)

## SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Repeated or prolonged contact with the mixture may cause removal of natural oil from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

Aspiration toxicity includes severe acute effects such as chemical pneumonia, varying degrees of pulmonary injury or death following aspiration.

**11.1.1. Substances**

ACETON	
Acute Toxicity – oral	<i>DL<sub>50</sub></i> > 5000mg/kg – rat
Acute Toxicity – dermal	<i>DL<sub>50</sub></i> > 5000mg/kg – rat
Acute Toxicity - inhalation	<i>CL<sub>50</sub></i> = 76mg/kg (vapour) – rat
PROPAN-2-OL	
Acute Toxicity – oral	<i>DL<sub>50</sub></i> > 5000mg/kg – rat
Acute Toxicity – dermal	<i>DL<sub>50</sub></i> > 5000mg/kg – rat
Acute Toxicity - inhalation	<i>CL<sub>50</sub></i> > 25mg/kg (vapour) – rat

**11.2. Information on other hazards**

No toxicological data available for the mixture.

**SECTION 12: ECOLOGICAL INFORMATION**

**12.1. Toxicity**

**12.1.2. Mixtures**

ACETON
LL <sub>50</sub> - 96h = > 1000mg/l, <i>Oncorhynchus mykiss</i> - OECD 203
PROPAN-2-OL
LL <sub>50</sub> - 96h = > 1000mg/l, <i>Pimephales promelas</i> - OECD 203 <i>EL<sub>50</sub></i> - 48h = > 1000mg/l, <i>Daphnia magna</i> - OECD 202

**12.2. Persistence and degradability**

No data available.

**12.3. Bioaccumulative potential**

No data available.

**12.4. Mobility in soil**

No data available.

**12.5. Results of PBT and vPvB assessment**

No data available.

**12.6. Endocrine disrupting properties**

No data available.

**12.7. Other adverse effects**

No data available.

**SECTION 13: DISPOSAL CONSIDERATIONS**

**13.1. Waste treatment methods**

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

Do not pour into drains or waterways.

**Waste:**

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

**Soiled packaging :**

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

**SECTION 14: TRANSPORT INFORMATION**

**14.1. UN number or ID number**

1950

**14.2. UN proper shipping name**

UN1950 = AEROSOL, Flammable

**14.3. Transport hazard class(es)**



2.1

**14.4. Packing group**

---

**14.5. Environmental hazards**

No

**14.6. Special precautions for user**

ADR/RID	Classe	Code	Groupe	Etiquette	Ident.	QL	Dispo.	EQ	Cat.	Tunnel
	2	5F	-	2.1	-	1 L	190 327 344 625	E0	2	D
IMDG	Classe	2°Etiq	Groupe	QL	FS	Dispo.	EQ	Arrimage manutention	Séparation	
	2	See SP63	-	See SP277	F-D. S-U	63 190 277 327 344 381 959	E0	- SW1 SW22	SG69	
IATA	Classe	2°Etiq.	Groupe	Passager	Passager	Cargo	Cargo	note	EQ	
	2.1	-	-	203	75 kg	203	150 kg	A145 A167 A802	E0	
	2.1	-	-	Y203	30 kg G	-	-	A145 A167 A802	E0	

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.

For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

**14.7. Maritime transport in bulk according to IMO instruments**

No

**SECTION 15: REGULATORY INFORMATION**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**Classification and labelling information included in section 2:**

The following regulations have been used:

EU Regulation No. 1272/2008 amended by EU Regulation No. 2021/643 (ATP 16)

EU Regulation No. 1272/2008 amended by EU Regulation No. 2021/849 (ATP 17)

**Container information:**

No data available.

**Particular provisions :**

No data available.

**15.2. Chemical safety assessment**

No data available.

**SECTION 16: OTHER INFORMATION**

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

**Wording of the phrases mentioned in section 3 :**

H220	Extremely flammable gas.
H280	Contains gas under pressure; may explode if heated
H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
EUH066	Repeated exposure may cause skin dryness or cracking.

**Abbreviations :**

REACH : Registration, Evaluation, Authorization and Restriction of Chemical Substances.

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

WGK : Wassergefahrdungsklasse (Water Hazard Class).

PBT: Persistent, bioaccumulable and toxic. vPvB : Very persistent, very bioaccumulable.

SVHC : Substance of Very High Concern.